

makefile

```
all: TableGen TableLoad TransFunds.class SerialGen SerialTest \  
    RunnerServer.class RunnerClient.class RunnerClient.jar  
  
TableGen: TableGen.cpp dtime.cpp  
    cp TableGen.cpp TableGen.sqC  
    (db2 connect to tabledb; db2 prep TableGen.sqC validate run datetime iso) || true  
    g++ -Wall -I/usr/db2dev/sqlllib/include TableGen.C dtime.cpp \  
        -L/usr/db2dev/sqlllib/lib \  
        -Wl,-rpath,/usr/db2dev/sqlllib/lib -ldb2 \  
        -oTableGen  
  
TableLoad: TableLoad.cpp dtime.cpp  
    cp TableLoad.cpp TableLoad.sqC  
    (db2 connect to tabledb; db2 prep TableLoad.sqC validate run datetime iso) || true  
    g++ -Wall -I/usr/db2dev/sqlllib/include TableLoad.C dtime.cpp \  
        -L/usr/db2dev/sqlllib/lib \  
        -Wl,-rpath,/usr/db2dev/sqlllib/lib -ldb2 \  
        -oTableLoad  
  
TransFunds.class: TransFunds.java DenomBreakdown.java DenomQty.java  
    javac -Xlint:deprecation TransFunds.java DenomBreakdown.java \  
        DenomQty.java  
    cp *.html *.class /var/www/html/js  
  
SerialGen: SerialGen.cpp  
    g++ SerialGen.cpp -oSerialGen  
  
SerialTest: SerialTest.cpp SerialRead.cpp SerialRecv.cpp  
    g++ SerialTest.cpp SerialRead.cpp SerialRecv.cpp -oSerialTest  
  
RunnerServer.class: RunnerServer.java CustomerOrder.java  
    javac -Xlint:deprecation RunnerServer.java CustomerOrder.java  
    cp *.html *.class /var/www/html/js  
  
RunnerClient.class: RunnerClient.java CustomerRequest.java ManagerThread.java  
    javac -Xlint:deprecation RunnerClient.java CustomerRequest.java \  
        ManagerThread.java  
    cp *.html *.class /var/www/html/js  
  
RunnerClient.jar: CustomerOrder.class ManagerThread*.class \  
    RunnerClient.class  
    jar cf RunnerClient.jar CustomerOrder.class ManagerThread*.class \  
    RunnerClient.class
```