

```
all: TestWorkshop.class hide seek OrderGen OrderStatus Greeting.class
```

```
TestWorkshop.class : Accessory.java AccessoryType.java Data.java Machines.java MachinesClass.java Station.java TestWorkshop.java Workshop.java  
javac Accessory.java AccessoryType.java Data.java Machines.java MachinesClass.java Station.java TestWorkshop.java Workshop.java
```

```
Crypto.o: Crypto.cpp  
g++ -c Crypto.cpp
```

```
corrupt: corrupt.cpp  
g++ corrupt.cpp -ocorrupt
```

```
hide: hide.cpp Crypto.o hideAndSeek.h  
g++ hide.cpp Crypto.o -ohide
```

```
seek: seek.cpp Crypto.o hideAndSeek.h  
g++ seek.cpp Crypto.o -oseek
```

```
OrderGen: OrderGen.cpp  
cp OrderGen.cpp OrderGen.sqlC  
(db2 connect to orderdb; \  
db2 prep OrderGen.sqlC validate run datetime iso) || true  
g++ -Wall -I/usr/db2dev/sqlllib/include OrderGen.C \  
-L/usr/db2dev/sqlllib/lib \  
-Wl,-rpath,/usr/db2dev/sqlllib/lib -ldb2 \  
-oOrderGen
```

```
OrderStatus: OrderStatus.cpp  
cp OrderStatus.cpp OrderStatus.sqlC  
(db2 connect to orderdb; \  
db2 prep OrderStatus.sqlC validate run datetime iso) || true  
g++ -Wall -I/usr/db2dev/sqlllib/include OrderStatus.C \  
-L/usr/db2dev/sqlllib/lib \  
-Wl,-rpath,/usr/db2dev/sqlllib/lib -ldb2 \  
-oOrderStatus
```

```
Greeting.class: Greeting.java  
javac Greeting.java
```