

all: RouteGen RouteTime PokerGen PokerRep RomanNum TestApp

RouteGen: RouteGen.cpp

```
cp RouteGen.cpp RouteGen.sqC
(db2 connect to egpc; \
  db2 prep RouteGen.sqC validate run datetime iso) || true
g++ -Wall -I/usr/db2dev/sqllib/include RouteGen.C \
  -L/usr/db2dev/sqllib/lib \
  -wl,-rpath,/usr/db2dev/sqllib/lib -ldb2 \
  -oRouteGen
```

RouteTime: RouteTime.cpp

```
cp RouteTime.cpp RouteTime.sqC
(db2 connect to egpc; \
  db2 prep RouteTime.sqC validate run datetime iso) || true
g++ -Wall -I/usr/db2dev/sqllib/include RouteTime.C \
  -L/usr/db2dev/sqllib/lib \
  -wl,-rpath,/usr/db2dev/sqllib/lib -ldb2 \
  -oRouteTime
```

PokerGen: PokerGen.cpp

```
g++ PokerGen.cpp -oPokerGen
```

PokerRep: PokerRep.cpp

```
G++ PokerRep.cpp -oPokerRep
```

RomanNum: RomanNum.cpp

```
g++ RomanNum.cpp -oRomanNum
```

TestApp.class: TestApp.java DisplayController.java LEDUnit.java
javac TestApp.java DisplayController.java LEDUnit.java